

## **REVOLUTION 300**





Available in 2 standard lengths, or built-to-order in custom length.

HELY CE

- 3 HP engine, direct-on-disc
- 100% Aluminium table chassis
- Stainless steel head rails and adjustable armoured ball bearings
- Polyethylene water basin with screw-in cap
  Water applies average factoring agreement.
- Water cooling system featuring armoured pipe, metallic tap and bilateral blade spray terminals
- Magnetic-induction pump
- PVC cable/pipe protection chain
- Cutting head's mechanical vertical tilting system allows for cut depth adjusting
- Cutting system's side tilt capability eases up to 45° ("mitre") cut
- Front, back and bilateral side blade protection devices included
- Electrical system featuring magneto thermal protection and release coil
- Retractable legs include fall-protection device
- Table handles and transport wheels included
- Supports Ø 300 and Ø 350 blades



	ART	F	kW	Нр	(RPM)	() mm		om	Com Com		Double Cut of	Kg	<b>(</b>	i
Revolution 300	1108	230V	2,2	3	2800	300 350	85 82	105 105	60x60 58x58	8,5 11	13 13	99	1	170x62xh90
Revolution 330	1109	230V	2,2	3	2800	300	115	135	81x81	8.5	13	105	1	180x62xh90
						330	112	133	19119	11	13			

## ITALIAN MANUFACTURER

Machinery and tools for professional tilers and bricklayers